

AccurioPrint C2070/C2060 DATASHEET

These first Konica Minolta production systems launched under the new Accurio brand name target small to midsize commercial printers as well as in-house print rooms and Central Reprographic Departments (CRDs). As entry-level printing systems, they offer outstanding new features including scan & print to/from USB Flash, a dual colour high-speed scanner, and the possibility to manage print jobs directly from the operating panel. CRDs will find it easy to adapt to changing document workflows in the company, enhance their overall productivity, and to extend their range of products and services by offering new, sophisticated print products.



AccurioPrint C2070/C2060

YOUR ADVANTAGES WITH AccurioPrint C2070/C2060





Recommended configurations



Technical specifications

STSTEIN SPECIFICATIONS	SYSTEM	SPECIFICATION	S
------------------------	--------	---------------	---

OTOTEW OF END TO ATTOMO	
Resolution	1,200 x 1,200 dpi x 8 bit
	1,200 x 3,600 dpi equivalent
Paper weight	62-350 gsm
Duplex unit	Non-stack type; 62–350 gsm
Paper sizes	330 x 487 mm; 330 x 1.200 mm (optional)
Maximum image area	323 x 480 mm
Paper input capacity	Standard: 1,500 sheets; Max.: 7,500 sheets
Paper output capacity	Max.: 3,100 sheets
Main unit dimensions	800 x 903 x 1,076 mm
(W x D x H)	
Main unit weight	316 kg

PRODUCTIVITY

AccurioPrint C2070

A4 - max. per minute	71 ppm
A3 - max. per minute	38 ppm
SRA3 - max. per minute	36 ppm
A4 - max. per hour	3,963 pph
A3 - max. per hour	2,107 pph
SRA3 - max. per hour	1,976 pph

AccurioPrint C2060

A4 - max. per minute	61 ppm
A3 - max. per minute	33 ppm
SRA3 - max. per minute	31 ppm
A4 - max. per hour	3,380 pph
A3 - max. per hour	1,792 pph
SRA3 - max. per hour	1.681 pph

CONTROLLER

CUNTRULLER	
Internal Konica Minolta	IC-603 A
Controller	
Internal Fiery Controller	IC-417
External Fiery Controller	IC-313
External Creo Controller	IC-314

SCANNER SPECIFICATIONS

Scan speed A4	Up to 240 ipm
Scan modes	TWAIN scan; Scan-to-HDD; Scan-to-FTP; Scan-to-SMB;
	Scan-to-eMail
Scan formats	TIFF (single and multi page); PDF
Scan resolution	600 x 600 dpi

COPIER SPECIFICATIONS

256 gradations

Gradations	256 gradations
FCOT	Less than 8 sec. (colour A4)
Magnification	25–400%, in 0.1% steps
Mutliple copies	1-9,999
ACCESSORIES	
Original cover	0C-511
Automatic document	DF-706
feeder	
Working table	WT-511
Heating unit for main	HT-511
body trays	
Air assist paper feed	PF-602m
unit	
Heating unit for	HT-504
PF-602m	
Air suction paper feed	PF-707
unit	
Heating unit for PF-707	HT-506
Heating unit for	HT-503
LU-202m/XL	
Bypass tray	MB-506
Relay unit	RU-509
Humidification unit	HM-102
Booklet finisher	FS-612
Staple finisher	FS-531
2/4-hole punch kit for	PK-512
FS-612/531	
2-hole punch kit for	PK-513
FS-612/531	
Post inserter for	PI-502
FS-612/531	
Envelope fuser	EF-103
Banner tray	MK-740
Large capacity unit	LU-202m
Large capacity unit	LU-202XL
Output tray	OT-510
High capacity output	0T-511
tray	
Envelope feeding kit	MK-746

⁻ All specifications refer to A4-size paper of 80 gsm quality.

The support and availability of the listed specifications and functionalities varies depending on operating systems, applications and network protocols as well as network and system configurations.

The stated life expectancy of each consumable is based on specific operating conditions such as page coverage for a particular page size (5% coverage of A4).

The actual life of each consumable will vary depending on use and other printing variables including page coverage, page size, media type, continuous or intermittent printing, ambient temperature and humidity.

Some of the product illustrations contain optional accessories.

Specifications and accessories are based on the information available at the time of printing and are subject to change without notice.
 Konica Minolta does not warrant that any prices or specifications mentioned will be error-free.

⁻ All brand and product names may be registered trademarks or trademarks of their respective holders and are hereby acknowledged.